according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Product code : 0253140864

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-

stance/Mixture

: Engine oil

1.3 Details of the supplier of the safety data sheet

Company : OOO «LLK-International»

Malaya Yakimanka str. 6

119180 Moscow Russian Fed.

www.lukoil-lubricants.com

Address of manufacture: Promishlennaya str. 84

614055 Perm Russian Fed.

Only representative:

LUKOIL LUBRICANTS EAST EUROPE S.R.L. Tipografilor Str., A-2 building, GF 11-15

013714 Bucharest

Romania

Telephone: +40 212272350

Fax: +40 212323295

Telephone : +7 495 627-40-20

Responsible/issuing person : info.product-safety@lukoil.com

1.4 Emergency telephone number

Telephone : 24h/5d

+7 495 627-40-20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements : **Disposal:**

P501 Dispose of contents/container to an ap-

proved facility in accordance with local, regional, national and international regula-

tions.

Additional Labelling:

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Material can create slippery conditions.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Hydrocarbons Additives

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	
The classification as a carcinogen need not apply if it can be shown that the substance contains			
less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in			
unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extrac-			
tion refractive index method", Institute of Petroleum, London. This note applies only to certain			
complex oil-derived substances in Part 3. :			
distillates (petroleum), hy-	64742-54-7	Asp. Tox.1; H304	>= 70 - < 90
drotreated heavy paraffinic	265-157-1		
	01-2119484627-25		
	0.47.40.70.7		4.5
paraffin oils (petroleum),	64742-70-7		>= 15 - < 30
catalytic dewaxed heavy	265-174-4		
	01-2119487080-42-0004		
L'atan Island Nam's	00070 00 0	A serie Observing HIAAO	4 05
bis(nonylphenyl)amine	36878-20-3	Aquatic Chronic4; H413	>= 1 - < 2,5
	253-249-4		
	01-2119488911-28		
zina O O O! O! totrakia/4 2	2245 25 2	Clain Irrit 2: LI245	. 1 .25
zinc O,O,O',O'-tetrakis(1,3-	2215-35-2	Skin Irrit.2; H315	>= 1 - < 2,5
dimethylbutyl)	218-679-9	Aquatic Chronic2; H411	

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

bis(phosphorodithioate) 01-2119953275-34

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Never give anything by mouth to an unconscious person.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with warm water and soap.

If on clothes, remove clothes.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice. Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do NOT induce vomiting.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Stomach/intestinal disorders

Vomiting Pneumonia irritant effects

Risks : May cause eye irritation.

Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Later control for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

: Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Special protective equipment

for firefighters

fighting

: In the event of fire, wear self-contained breathing apparatus.

Extinguishing media - large fires

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : First aider needs to protect himself.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation, especially in confined areas.

Use personal protective equipment.

The danger areas must be delimited and identified using rele-

vant warning and safety signs.

Refer to section 15 for specific national regulation.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage.

Avoid subsoil penetration. Do not contaminate water.

Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with oil absorbent material.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Use only in area provided with appropriate exhaust ventilation.

Provide exhaust ventilation close to floor level.

Do not get on skin or clothing.

Avoid inhalation, ingestion and contact with skin and eyes.

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Advice on protection against

fire and explosion

: To avoid ignition of vapours by static electricity discharge, all

metal parts of the equipment must be grounded.

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition.

Keep in a bunded area.

Do not smoke.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Hygiene measures : Do not get in eyes.

Take off all contaminated clothing immediately. Keep contaminated clothing under water.

Remove all contaminated clothing under the shower.

Fire-fighting class : Fires involving liquids or liquid containing substances. Also

includes substances which become liquid at elevated temper-

atures.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep containers tightly closed in a cool, well-ventilated place.

Further information on stor-

age conditions

: Keep away from heat and sources of ignition.

Advice on common storage : D

 Do not store together with explosives, gases, oxidizing solids, products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive prod-

ucts.

Do not store together with oxidizing and self-igniting products. Do not store together with explosives, oxidizing agents, organ-

ic peroxides and infectious products.

Do not store together with acids and ammonium salts.

Other data : Keep away from direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

bis(nonylphenyl)amine : End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Value: 0,62 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 4,37 mg/m3 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,31 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 1,09 mg/m3 End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 0,31 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

bis(nonylphenyl)amine : Fresh water

Value: 0,1 mg/l Marine water Value: 0,01 mg/l Fresh water sediment Value: 132000 mg/kg Marine sediment Value: 13200 mg/kg

Soil

Value: 263000 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,40 mm
Directive : DIN EN 374

Viton (R) 480 min 0,70 mm DIN EN 374 butyl-rubber 120 min 0,70 mm DIN EN 374 Neoprene 60 min 0,60 mm DIN EN 374

Remarks : Take note of the information given by the producer concerning

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous

outside influences (e.g. temperature).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Skin and body protection : Flame retardant protective clothing

Workers should wear antistatic footwear.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Respirator with filter type A

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Suitable respiratory equipment:

Self-contained breathing apparatus (EN 133)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : tan

Odour : No data available
Odour Threshold : No data available
pH : No data available

pour point : -41 °C

: No data available

Flash point : 228 °C

Method: Cleveland open cup

Evaporation rate : No data available
Burning rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Vapour density : No data available
Relative density : No data available
Density : 0,849 g/cm3 (20 °C)

Bulk density : No data available

Water solubility : < 0,01 g/l (20 °C, 1.013 mbar)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: not determined

Auto-ignition temperature : 347 °C

Ignition temperature : No data available
Thermal decomposition : No data available
Viscosity, dynamic : No data available
Viscosity, kinematic : 67 mm2/s (40 °C)

Flow time : No data available Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Self-heating substances : No data available
Impact sensitivity : No data available
Surface tension : No data available

: No data available

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is chemically stable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : No data available

Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

Acute toxicity (other routes of :

administration) No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 Oral Rat: > 5.000 mg/kg

Method: CONCAWE

Acute inhalation toxicity : LC50 Rat: > 5,53 mg/l

Exposure time: 4 h Method: CONCAWE

Acute dermal toxicity : LD50 Dermal Rat: > 2.000 mg/kg

Method: CONCAWE

paraffin oils (petroleum), catalytic dewaxed heavy:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg

Method: CONCAWE

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Information given is based on data obtained from similar sub-

stances.

Acute inhalation toxicity : LC50 Rat: > 5,53 mg/l

Exposure time: 4 h Method: CONCAWE

Information given is based on data obtained from similar sub-

stances.

Acute dermal toxicity : LD50 Rabbit: > 2.000 mg/kg

Method: CONCAWE

Information given is based on data obtained from similar sub-

stances.

bis(nonylphenyl)amine:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg

Method: OECD Test Guideline 401

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rat: > 2.000 mg/kg

Method: OECD Test Guideline 402

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

slight irritation

Non persistent irritation

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

Result: Mild skin irritation Method: CONCAWE

Based on available data, the classification criteria are not met.

bis(nonylphenyl)amine:

Species: Rabbit

Result: No skin irritation

Method: OECD Test Guideline 404

Test substance:yes

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Non persistent irritation

Components:

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

paraffin oils (petroleum), catalytic dewaxed heavy:

Result: No eye irritation Method: CONCAWE

Information given is based on data obtained from similar substances.

bis(nonylphenyl)amine:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Test substance: yes

Based on available data, the classification criteria are not met.

zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):

Classification: Causes serious eye damage.

Based on available data, the classification criteria are not met.

Concentration limits

SCL

European Chemicals Agency - ECHA

Respiratory or skin sensitisation

Product:

No known sensitising effect.

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

Result: negative Method: CONCAWE

Information given is based on data obtained from similar substances.

bis(nonylphenyl)amine:

Test Method: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Method: OECD Test Guideline 406

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : No data available

Genotoxicity in vivo : No data available

Germ cell mutagenicity- As-

sessment

: No data available

Components:

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

paraffin oils (petroleum), catalytic dewaxed heavy:

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse Method: CONCAWE Result: negative

bis(nonylphenyl)amine:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Test species: Mouse

Result: negative

Carcinogenicity

Product:

This information is not available.

Carcinogenicity - Assess-

ment

: No data available

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

Species: Mouse

Application Route: Skin contact

Method: CONCAWE Result: negative

bis(nonylphenyl)amine:

This information is not available.

Reproductive toxicity

Product:

Effects on fertility

This information is not available.

Effects on foetal develop-

ment

: This information is not available.

Reproductive toxicity - As-

sessment

: No data available

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

Effects on foetal develop: : Application Route: Oral

ment Method: OECD Test Guideline 421

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Result: negative CONCAWE

bis(nonylphenyl)amine:

Effects on fertility

This information is not available.

STOT - single exposure

Product:

No data available

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

No data available

bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

No data available

Components:

bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

This information is not available.

Repeated dose toxicity - : No data available

Assessment

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

No observed adverse effect level: Rabbit: 1000 mg/kg

Application Route: Skin contact Method: OECD Test Guideline 407

No observed adverse effect level: : > 0,28 mg/l

Application Route: Inhalation

(local)

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

No observed adverse effect level: : > 0,98 mg/l

Application Route: Inhalation

(systemic)

No observed adverse effect level: : > 2000 mg/kg

Application Route: Skin contact

Exposure time: 90 d Subchronic toxicity

Aspiration toxicity

Product:

No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

May be fatal if swallowed and enters airways.

paraffin oils (petroleum), catalytic dewaxed heavy:

No data available

bis(nonylphenyl)amine:

No data available

Further information

Product:

No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Chronic tox-

: No data available

icity)

Toxicity to daphnia and other

aquatic invertebrates (Chron-

: No data available

ic toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to algae : NOEL (algae): > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

: NOEL: 10 mg/l

Species: Fish

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: NOEL: 10 mg/l

paraffin oils (petroleum), catalytic dewaxed heavy:

Toxicity to fish : (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: LL50

Method: No information available.

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

Method: No information available.

CONCAWE

LL50 : > 10.000 mg/l Exposure time: 96 h Test Type: semi-static test Method: No information available.

European Chemicals Agency - ECHA

NOEL : > 10.000 mg/l

Exposure time: 96 h

Test Type: semi-static test Method: No information available. European Chemicals Agency - ECHA

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test Type: Growth inhibition Method: No information available.

CONCAWE

Toxicity to bacteria : NOEL (Photobacterium phosphoreum): > 1,93 mg/l

Exposure time: 4 d

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Test Type: Respiration inhibition of activated sludge

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,02 mg/l

Species: Daphnia magna (Water flea)

bis(nonylphenyl)amine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 4 d Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 2 d Test Type: static test Test substance: yes

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (Scenedesmus subspi-

catus)): > 100 mg/l Exposure time: 3 d Test Type: static test

Method: OECD Test Guideline 201

Toxicity to bacteria : EC50 (activated sludge): > 1.000 mg/l

Exposure time: 0,1 d

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: No data available

12.2 Persistence and degradability

Product:

Biodegradability : Result: Not readily biodegradable.

Physico-chemical removabil-

ity

: The product is insoluble and floats on water.

May be separated mechanically in waste water plants.

Impact on Sewage Treat-

ment

: No data available

Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

Biodegradability : Result: not rapidly degradable

Stability in water : The product is insoluble and floats on water.

bis(nonylphenyl)amine:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Result: Not biodegradable Biodegradation: 1 % Exposure time: 28 d

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Product:

Bioaccumulation : No data available

Partition coefficient: n-

octanol/water

: not determined

Components:

bis(nonylphenyl)amine:

Bioaccumulation : Bioconcentration factor (BCF): 1.584,89

Partition coefficient: n-

octanol/water

: $\log Pow: > 7,6$

12.4 Mobility in soil

Product:

Mobility : Should not be released into the environment.

Components:

bis(nonylphenyl)amine:

Stability in soil : Adsorbs on soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

bis(nonylphenyl)amine:

Assessment : This substance is not considered to be persistent, bioaccumu-

lating and toxic (PBT).

This substance is not considered to be very persistent and

very bioaccumulating (vPvB).

12.6 Other adverse effects

Product:

Additional ecological infor- : Should not be released into the environment.

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

mation Do not let product enter drains.

Components:

bis(nonylphenyl)amine:

Additional ecological infor-

mation

: Should not be released into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

13 02 06*

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

15 01 10*

SECTION 14: Transport information

14.1 UN number

ADR : Not dangerous goods RID : Not dangerous goods IMDG : Not dangerous goods IATA : Not dangerous goods ADN : Not dangerous goods

14.2 Proper shipping name

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.3 Transport hazard class

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.4 Packing group

ADR : Not dangerous goods RID : Not dangerous goods

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

IMDGIATAADNNot dangerous goodsNot dangerous goodsNot dangerous goods

14.5 Environmental hazards

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.6 Special precautions for user

Remarks : not required

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : This product is being carried under the scope of MARPOL

Annex I

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

Directive 1999/13/EC on the limitation of emissions of : not required under normal use

volatile organic compounds

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H411 : Toxic to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

according to Regulation (EC) No. 1907/2006



Motor oil LUKOIL GENESIS GLIDETECH 5W-30

Version Revision Date: Product code: Date of last issue: -

1.0 12.10.2016 0253140864 Date of first issue: 12.10.2016

Print Date: 12.10.2016

Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Skin Irrit. : Skin irritation

Further information

Other information : Changes since the last version are highlighted in the margin.

This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.